XS Instruments pH 50

pH/mV/°C Bench top Meter

Basic and Easy

A group of European experts in electrochemistry and a famous Asian producer have developed this new line of bench top meters, finding the right balance between the design and **easy to use**.

The LCD back light display **easy on to read** shows all information that you need about measurement, included icon for stability. Up to 3 point pH calibration with automatic recognition for USA buffers. Icon support all calibration editing function with alarm electrode diagnostics. **Easy to calibrate.**

Main Features

- Display pH/mV and Temperature parameters simultaneously
- Resolution: 0,01 pH
- Automatic Calibration up to 3 point automatic recognized for USA buffers.
- Indication stability of the measurement with icon
- Non-volatile memory holds up to 25 data points
- IP54 rated housing handles splashes
- 3 years meter replacement warranty





Technical specification

Technical specifications	pH 50
pH measuring range	0,00 14,00 pH
Resolution	0,01 pH
Calibration points	13
Buffer ricognized	USA: pH 4,01 / 7,00 / 10,01
Indication of measurement stability	Yes
mV measuring range	± 2.000 mV
Resolution	1 mV
Temperature measuring range	0 100,0 °C
Resolution / Accuracy	0,1 °C
Temperature compensation	Automatic / manual 0 100 °C
Memory	25 data
Display	LCD (Liquid Crystal Display) / Backlight
Inputs	BNC and Jack phone (ATC)
Power supply	AC/DC adapter 9 V / 300 mA
IP protection class	IP 54
Dimensions / weight instrument	160 x 190 x 70 mm / 750 gr



How to order	
Code	Description
50001002	pH 50 complete kit included pH electrode 201T with temperature sensor inside and BNC, colored pH buffer solution pH 7 and pH 4 and electrode holder.
50001012	pH 50 kit without pH electrode. Cable S7/BNC, temperature probe NT55, colored pH buffer solution pH 7 and pH 4 and electrode holder
50002002	pH Electrode mod. 201T with integrated temperature sensor, cable length 1 m BNC plug
50002012	NT 55 Temperature probe